



AF0036

Soft Floor Covering Adhesive

PRODUCT DESCRIPTION

DURAPRO AF0036 is a non-flammable interior flooring adhesive for bonding carpet and sheet covering over plywood underlayment or well cured concrete.

PRODUCT FEATURES

- Easy to spread
- High tack
- Non – Flammable
- VOC compliant

PREPARATION

Subfloors must be structurally sound, linear, porous, clean, dry and free of contaminants. Adhesive and flooring (unwrapped) must be at room temperature (20°C) 24 hours before, during, and after installation. Concrete floors must be fully cured and free from moisture and hydrostatic pressure..

APPLICATION

Stir before using. Spread adhesive with a 2 mm (1/16") V notch trowel held at 45° angle for smooth backing. For floor covering with rough backing use a 5 mm (3/16") V notch trowel. Spread the adhesive and put the floor covering in place within 30 minutes. Lay the flooring material as per manufacturer's instructions. Use a 45 kg (100 lbs) roller in several directions to eliminate trowel marks and air entrapment, and to ensure optimal transfer of the adhesive. Let dry 24 hours before allowing heavy foot traffic or moving furniture.

COVERAGE

Approximately 2-4 m²/L (80-160 sq.ft./gallon)

ATTENTION

Refer to flooring manufacturer's recommendation for layout, expansion space requirements, and detailed installation instructions. For indoor use only. Not to be used on particleboard.

CLEAN UP

Clean hands, tools and excess adhesive with warm soapy water before the product dries. If glue has hardened, use a putty knife and mineral spirits with caution, taking care not to affect the surface finish.

STORAGE

Shelf life is 18 months at room temperature in original unopened container. Product is freeze/thaw stable if frozen not lower than -10°C.

PHYSICAL PROPERTIES

Viscosity	60,000 – 70,000 cps (RVT, #7/20 rpm/25°C)
Solids	54% - 56%
Colour	Light tan
Odour	Hydrocarbon
Specific Gravity	1.25 ± 0.02
pH	6.5 - 7.5
Water Resistance	Excellent (when dried)
Open Time	30 – 40 minutes
VOC	< 50 g / L

PRECAUTIONS

This product is not classified dangerous according to the Consumer Chemicals and Containers Regulations (CCCR). Note to professional user: refer to Safety Data Sheet (SDS) for more information.

ENVIRONMENT

VOC compliant for low emissions adhesives and sealants standards in place at the date of production. *This product contains no added urea-formaldehyde. The use of this product may contribute in obtaining LEED credits.

ORDERING INFORMATION

UPC	Size	units per package	Units per row	Units per pallet
058751361000	950 ml	6	72	432
058751363783	3.78 L	2	20	100
058751360157	15.0 L	1	12	36

WARRANTY

Surface conditions, product application, storage and transport are beyond the manufacturer's control; liability, if any, is limited to replacement of product ONLY.

DISCLAIMER

Our personnel is available to help purchasers obtain best results from our products, and recommendations are based on tests and information believed to be reliable. However, since we have no control over the conditions under which our products are transported to, stored, handled, or used by purchasers, all recommendations and sales are made on condition that we will not be held liable for any damages resulting from their use. No representative of ours has any authority to waive or change this provision.

DATE

April 2017