

**\*\*Note that the EVO Stain Remover becomes RESTOR-DECK by LIGNA\*\***

Wood stain remover without vocs, ecological and biodegradable !

**LIGNA® RESTOR-DECK** is an excellent wood stain remover for most water and oil based stains. It can also be used on bare wood surfaces to thoroughly clean and remove discoloration. This stripper is particularly recommended for removing black stains caused by weathering, fungus and even spills from cooking on the BBQ.

**RESTOR-DECK** is the perfect solution to rejuvenate and restore your wood surfaces prior to the application of a finishing oil such as HYBRI-DECK or EXTERIA. Also, if you are unhappy with the colour of your wood surfaces and want to start from scratch without too much sanding, this product is for you. As a biodegradable water-based product, RESTOR-DECK will not harm surrounding vegetation and contains no VOCs. Although this stripper is intended for outdoor use, it can be used indoors in a well-ventilated area.

RESTOR-DECK is not a brightener and may darken some wood species.

Removes water and oil stains

Removes unwanted discolouration and stains

Rapid stripping with little or no scrubbing

VOC-free, ecological and biodegradable

Removes black spots and discolouration caused by weathering

Easy to use

Preparation :

Stripping: Dilute 1 part of RESTOR-DECK to 1 part of water [1:1]. We do not recommend applying the product undiluted. If this is the case, avoid the product drying on the surface at all costs.

Cleaning: Dilute 1 part of RESTOR-DECK to 10 parts of water [1:10]. Increase concentration if necessary.

Application :

Protect surrounding vegetation by spraying with water before applying RESTOR-DECK.

Apply with a garden sprayer, broom or wide brush.

Wait and allow to react for 15 minutes.

Do not allow to dry on surface and reapply as required.

Scrub the surface and rinse with water. We recommend rinsing with a pressure washer. Rinse until the foam disappears.

Wait until the wood is completely dry before applying a new finish.

In the case of stripping, sanding will be required prior to the application of a new finish as recommended by the product manufacturer.

Tool cleaning :Water and soap.

Coverage :

± 40 ft<sup>2</sup> / Litre (Pure) ± 80 ft<sup>2</sup> / Litre (Diluted 1:1)

946 mL [LIG-RES-946] & 3,78 mL [LIG-RES-378]